



Hot Oven Chain Lubricant

GRAPHITE-BASED LUBRICANT

Hot Oven Chain Lubricant is a grey/black coloured, synthetic graphite-based coating used to lubricate oven chains, bushings and pins. The lubricant is designed to deeply penetrate the coated item and extend product life.

PHYSICAL PROPERTIES

Property	Value
Solids Content	9.8%
Colour	Grey/Black
Liquid Carriers	Polyalkylene glycol and water
Temperature Range	100–232°C (212–450°F)
Viscosity (cps)	<50

BENEFITS

- Extends product life
- National Science Foundation H2 rating
- Dries quickly on hot surfaces
- Evaporates cleanly
- Water-based
- No smoke or odor creation
- Non-flammable
- Does not attract dirt or grit

USE INSTRUCTIONS

1. Thoroughly clean the surfaces being coated prior to application.
2. Mix the coating thoroughly.
3. Apply the coating by brush, roller or airless spray equipment. Use fans to prevent dust buildup during spray applications.
4. The coating should be between 93–204°C (200–400°F) for application. Lower temperatures may cause incomplete drying.
5. Clean up any spills with soap and water.

STORAGE

- Twelve month shelf life from date of shipment
- Do not freeze

AVAILABILITY

- 3.78 liter (1 gallon) cans—4 per case
- 19 liter (5 gallon) pails

