



PYROCUT B 200 S

SAW LUBRICANT

Pyrocut B 200 S is a fatty-oil blend saw lubricant. It assists in cutting aluminium (including heavy billets) and other nonferrous metals, and can be misted for minimum quantity lubrication (MQL) applications.

Pyrocut B 200 S is excellent for applications requiring lubricity instead of extremely high pressure, and works with ferrous light drawing or forming applications that can't accommodate "vanishing lubes." The lubricant's low viscosity allows it to easily drain from parts while leaving a minimal film.

Pyrocut B 200 S has excellent oxidation resistance and can be flashed off in a hot oven without staining or leaving a residue like unsaturated vegetable ester products. This lubricant can be removed with surfactant or mild alkaline cleaners, and has less effect on paint and polymers than unsaturated vegetable ester products.

BENEFITS

- Excellent cutting performance
- Oxidation resistant
- Easy cleanup

PHYSICAL PROPERTIES

Property	Value
Specific Gravity	0.85
Weight-kg/L (lb/gal)	0.84 (7.05)
Viscosity-SUS at 38°C (100°F)	40
Appearance	Clear, water white to slightly yellow
Odour	Slight

AVAILABILITY

- 55 gal (208.20 L) drums
- One gal plastic jugs (four jugs to a box)

