

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV GL AS under the authority of the Government of Norway.

This is to certify:

That the Surface materials and floor coverings with low flame-spread characteristics: decorative veneers

with type designation(s)
Decidamp® DC30

Issued to
Pyrotek Pty Ltd
Girraween NSW, Australia

is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2017/306**,
item No. MED/3.18a. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2023-04-10**.

Issued at **Høvik** on **2018-04-11**

DNV GL local station:
Sydney

Approval Engineer:
Tessa Bieber



Notified Body
No.: **0575**

for **DNV GL AS**

Roald Vårheim
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



Product description

"Decidamp® DC30"

is composed of a two part component polyurethane damping paste applied between two layers of aluminium as follows:

- Aluminium sheet (facing) – 2 mm
- Sound proofing product (core) – 3 mm
- Aluminium sheet (facing) – 2 mm

Overall thickness: Approx. 7 mm.
Color: Grey
Max. organic content: 43%

The two-component polyurethane based damping paste has the following properties:

Weight per unit area: 201.6 g/m²
Application thickness: 3.0 mm
Product mixing ratio: 9:1 (Part A to Part B)

For further details see Type Examination documentation below.

Application/Limitation

Low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Approved for use as decorative veneers on any non-combustible substrate.

Any adhesive used, other than the one used during testing, has to be tested for low flame spread characteristics according to IMO FTP Code Part 5 and to be approved according to the Marine Equipment Directive and bear the Mark of Conformity.

The product satisfies the requirement for maximum gross calorific value (ref. SOLAS II-2/5.3.2.2) without further testing.

Each product is to be supplied with its manual for installation and maintenance.

Type Examination documentation

Test report Nos.:

- 166741 dated 3 September 2007 from Bodycote Warringtonfire, UK (as tested name "Soundamp DC30 and Soundamp CLD2")
- 327544 issue 2 dated 11th April 2013 from Exova Warringtonfire, Warrington, UK (additional test report to 166741)

Tests carried out

Tested according to IMO 2010 FTP Code Parts 5 and Annex 2 Item 2.2 and 2.3.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, Mark of Conformity and USCG approval number if applicable (see below).